



MODULE LABEL KEY	
ANALOGUE MODULE	AN 1 etc
INPUT/OUTPUT MODULE	I/O 1 etc
P.S.U. & BASIC I/O MODULE	P.S.U.

ABBREVIATIONS	
CT	CURRENT INPUTS
VT	VOLTAGE INPUTS
SI	STATUS INPUTS
CO	CHANGE OVER OUTPUT CONTACTS
NO	NORMALLY OPEN OUTPUT CONTACTS
NC	NORMALLY CLOSED OUTPUT CONTACTS

MATERIAL:

Dimensions in millimetres ; Surface texture in micrometres.  
Machine where marked ✓  
For explanation of dimensions, tolerances, notes etc. see B.S.308.  
Limit on untoleranced unmachined dimensions ±  
Limits on untoleranced machined dimensions to B.S.4500;  
i.e. up to 6±0.1; over 30 to 120±0.3; over 315±0.8;  
over 6 to 30±0.2; over 120 to 315±0.5;  
General unmachined angular tolerance ±

FOR INFORMATION ONLY  
UNCONTROLLED COPY  
NOT SUBJECT TO UPDATE

Finish:	Title:	First used on:
Treatment:	TERMINAL I.D. & WIRING FOR IOTA 200 SERIES RELAY (4CT,4VT,19SI,3CO,18NO) E12 CASE.	Similar Articles:
	<b>VATECH REYROLLE</b> <b>AUTOMATION, CONTROL &amp; PROTECTION</b>	Supersedes:
	Original Scale: NTS	Drg. No. 2761W11026
Copyright © 2005 VATECH REYROLLE ACP Ltd. Hebburn	1 14/04/05 CHANGE	ISSUE DATE NOTED
DRAWN MM/RDW	CHECKED RDW	APPROVED RD.WATSON
DATE 14/04/05	IE	OPS PCP
Purch.Spec. TQ	EAC	CE STD A1