



| MODULE LABEL KEY | |
|---------------------------|-----------|
| ANALOGUE MODULE | AN 1 etc |
| INPUT/OUTPUT MODULE | I/O 1 etc |
| P.S.U. & BASIC I/O MODULE | P.S.U. |

| ABBREVIATIONS | |
|---------------|---------------------------------|
| CT | CURRENT INPUTS |
| VT | VOLTAGE INPUTS |
| SI | STATUS INPUTS |
| CO | CHANGE OVER OUTPUT CONTACTS |
| NO | NORMALLY OPEN OUTPUT CONTACTS |
| NC | NORMALLY CLOSED OUTPUT CONTACTS |

FOR INFORMATION ONLY
UNCONTROLLED COPY
NOT SUBJECT TO UPDATE

MATERIAL:

Dimensions in millimetres ; Surface texture in micrometres.
Machine where marked ✓
For explanation of dimensions, tolerances, notes etc. see B.S.308.
Limit on untoleranced unmachined dimensions ±
Limits on untoleranced machined dimensions to B.S.4500;
i.e. up to 6±0.1; over 30 to 120±0.3; over 315±0.8;
over 6 to 30±0.2; over 120 to 315±0.5;
General unmachined angular tolerance ±

| | | |
|------------|--|---------------------|
| Finish: | Title: | First used on: |
| Treatment: | TERM IDENT & WIRING DIAGRAM FOR IOTA RELAY (4VT,43SI,3CO,42NO) E16 CASE | Similar Articles: |
| | VA TECH Reyrolle AUTOMATION, CONTROL & PROTECTION | Supersedes: |
| | Original Scale: NTS | Drg. No. 2761W11022 |

Copyright © 2005 VA TECH Reyrolle Ltd. Hebburn

| | | |
|-------|----------|--------|
| 1 | 24/02/05 | CHANGE |
| ISSUE | DATE | NOTED |

DRAWN ML/MM CHECKED RDW APPROVED RD.WATSON DATE 25/2/05 IE OPS PCP Purch.Spec. TQ EAC CE STD A1